

Ø 2.3  
mm

134 °C  
273 °F

## Uchwyt stały

### Pętla asymetryczna

- drut pleciony



końcówka izolowana



końcówka standardowa

długość	15 mm	25 mm	15 mm	25 mm
180 cm	OK 30 22-C	OK 31 22-C	OK 32 22-C	OK 33 22-C
230 cm	OK 30 22-G	OK 31 22-G	OK 32 22-G	OK 33 22-G

### Pętla owalna

- drut pleciony



końcówka izolowana



końcówka standardowa

długość	20 mm	25 mm	35 mm	20 mm	25 mm	35 mm
180 cm	OK 34 2205-C	OK 34 2206-C	OK 34 2207-C	OK 34 2215-C	OK 34 2216-C	OK 34 2217-C
230 cm	OK 34 2205-G	OK 34 2206-G	OK 34 2207-G	OK 34 2215-G	OK 34 2216-G	OK 34 2217-G

### Pętla heksagonalna

- drut pleciony



końcówka izolowana



końcówka standardowa

długość	20 mm	25 mm	35 mm	20 mm	25 mm	35 mm
180 cm	OK 38 2205-C	OK 38 2206-C	OK 38 2207-C	OK 37 2205-C	OK 37 2206-C	OK 37 2207-C
230 cm	OK 38 2205-G	OK 38 2206-G	OK 38 2207-G	OK 37 2205-G	OK 37 2206-G	OK 37 2207-G

### Pętla owalna

- drut monofilament



końcówka standardowa

długość	20 mm	25 mm	30 mm
180 cm	OK 34 2215M-C	OK 34 2216M-C	OK 34 2217M-C
230 cm	OK 34 2215M-G	OK 34 2216M-G	OK 34 2217M-G

