

**Zestawienie stali stal S235JR**

| Pozycja                | Profil | Długość [mm] | Masa [kg/m] | Sztuk | Masa [kg]      |
|------------------------|--------|--------------|-------------|-------|----------------|
| Ns-0.1                 | C140   | 1200         | 16,0        | 14    | 268,8          |
| Ns-0.2                 | C140   | 1350         | 16,0        | 4     | 86,4           |
| Ns-0.3                 | C140   | 1300         | 16,0        | 2     | 41,6           |
| Ns-0.4                 | C140   | 1200         | 16,0        | 2     | 38,4           |
| Ns-0.5                 | C140   | 1700         | 16,0        | 2     | 54,4           |
| Ns-0.6                 | C100   | 1400         | 10,6        | 76    | 1127,8         |
| Ns-0.7                 | C100   | 900          | 10,6        | 4     | 38,2           |
| Ns-0.8                 | C100   | 1050         | 10,6        | 12    | 133,6          |
| Ns-0.9                 | C100   | 1900         | 10,6        | 4     | 80,6           |
| Ns-1.1                 | C140   | 1450         | 16,0        | 10    | 232,0          |
| Ns-1.2                 | C180   | 1500         | 22,0        | 2     | 66,0           |
| Ns-1.3                 | C140   | 1800         | 16,0        | 2     | 57,6           |
| Ns-1.4                 | C160   | 1850         | 18,8        | 2     | 69,6           |
| Ns-1.5                 | C140   | 1600         | 16,0        | 2     | 51,2           |
| Ns-2.1                 | C140   | 1450         | 16,0        | 2     | 46,4           |
| Ns-2.2                 | C140   | 1350         | 16,0        | 2     | 43,2           |
| Ns-2.3                 | C220   | 2100         | 29,4        | 2     | 123,5          |
| Ns-2.4                 | C140   | 1500         | 16,0        | 2     | 48,0           |
| Bs-2.1                 | C200   | 2900         | 25,3        | 2     | 146,7          |
| Bs-2.2                 | C200   | 2800         | 25,3        | 2     | 141,7          |
| Bs-2.3                 | C280   | 3900         | 41,8        | 2     | 326,0          |
| Bs-2.4                 | C220   | 2900         | 29,4        | 2     | 170,5          |
| Bs-2.5                 | C300   | 6200         | 46,2        | 2     | 572,9          |
| Bs-2.6                 | C200   | 3500         | 25,3        | 2     | 177,1          |
| Bs-2.7                 | C200   | 3400         | 25,3        | 4     | 344,1          |
| Bs-2.9                 | C200   | 3450         | 25,3        | 2     | 174,6          |
| Bs-2.11                | C200   | 3300         | 25,3        | 2     | 167,0          |
| Bs-2.12                | C280   | 3450         | 41,8        | 2     | 288,4          |
| Bs-2.13                | C260   | 6000         | 37,9        | 3     | 682,2          |
| Bs-2.14                | C320   | 2400         | 59,5        | 1     | 142,8          |
| Bs-2.15                | C320   | 4850         | 59,5        | 2     | 577,2          |
| Bs-2.16                | C280   | 4650         | 41,8        | 2     | 388,7          |
| Bs-2.17                | C280   | 4550         | 41,8        | 2     | 380,4          |
| Bs-2.18                | C280   | 4500         | 41,8        | 2     | 376,2          |
| Bs-2.19                | C280   | 4250         | 41,8        | 2     | 355,3          |
| Bs-2.20                | C280   | 3950         | 41,8        | 1     | 165,1          |
| Bs-2.21                | C280   | 4540         | 41,8        | 1     | 189,8          |
| Bs-2.22                | C280   | 4500         | 41,8        | 1     | 188,1          |
| Bs-2.23                | C280   | 4200         | 41,8        | 2     | 351,1          |
| Bs-2.24                | C280   | 5150         | 41,8        | 1     | 215,3          |
| Bs-2.25                | C200   | 4150         | 25,3        | 4     | 420,0          |
| Bs-2.26                | C260   | 5850         | 37,9        | 2     | 443,4          |
| Bs-2.27                | C300   | 1200         | 46,2        | 1     | 55,4           |
| Bs-2.28                | C300   | 1050         | 46,2        | 1     | 48,5           |
| Bs-1.3                 | IPE160 | 550          | 15,8        | 14    | 121,7          |
| Suma:                  |        |              |             |       | <b>10217,3</b> |
| Masa spoin i blach     |        |              |             |       | 1021,7         |
| <b>Masa całkowita:</b> |        |              |             |       | <b>11239,1</b> |

**Zestawienie stali stal S355JR**

| Pozycja                | Profil | Długość [mm] | Masa [kg/m] | Sztuk | Masa [kg]     |
|------------------------|--------|--------------|-------------|-------|---------------|
| Bs-1.1                 | HEB320 | 6250         | 134,0       | 1     | 837,5         |
| Bs-1.2                 | HEB320 | 12300        | 134,0       | 1     | 1648,2        |
| S-1.3                  | HEB220 | 2500         | 71,5        | 1     | 178,8         |
| Suma:                  |        |              |             |       | <b>2664,5</b> |
| Masa spoin i blach     |        |              |             |       | 266,4         |
| <b>Masa całkowita:</b> |        |              |             |       | <b>2930,9</b> |